

SIZE (IN) EFF. AREA	MDC P/N "Size (in.)" RFSO Flanges" "Pressure Rating"Series" "O/A length"Bellows Mat."	SERIES	MOVEMENTS			APPROX. WEIGHT (LBS.)	SPRING RATES		
			AXIAL COMP. (IN.)	LAT. DEFL. (IN.)	ANG. ROT. (DEG.)		AXIAL LBS/ IN.	LAT. LBS/ IN.	ANG. IN/LBS /DEG.
3	3.00"W-0150S-8.00"-M5	S	0.75	0.06	5	5	520	3900	24
12.2	3.00"W-0150L-10.00"-M5	L	1.50	0.25	10	6	260	488	12
4	4.00"W-0150S-9.00"-M5	S	0.88	0.08	5	8	480	5200	78
20.2	4.00"W-0150L-12.00"-M5	L	1.75	0.32	10	9	240	650	39
5	5.00"W-0150S-9.00"-M5	S	1.00	0.12	6	12	740	8346	140
30.6	5.00"W-0150L-12.00"-M5	L	2.00	0.48	12	14	370	1043	70
6	6.00"W-0150S-9.50"-M5	S	1.00	0.11	6	18	840	9360	204
43.0	6.00"W-0150L-13.00"-M5	L	2.00	0.44	12	20	420	1170	102
8	8.00"W-0150S-10.00"-M5	S	1.25	0.13	5	24	1340	17920	540
72.6	8.00"W-0150L-14.00"-M5	L	2.50	0.52	10	28	670	2240	270
10	10.00"W-0150S-10.00"-M5	S	1.25	0.09	5	31	1080	18496	720
111	10.00"W-0150L-14.00"-M5	L	2.50	0.36	10	37	540	2312	360
12	12.00"W-0150S-10.50"-M5	S	1.50	0.09	5	42	2000	42000	1776
154	12.00"W-0150L-15.00"-M5	L	3.00	0.36	10	54	1000	5250	888
14	14.00"W-0150S-10.50"-M5	S	1.50	0.08	4	60	2400	56000	2400
183	14.00"W-0150L-15.00"-M5	L	3.00	0.32	8	75	1200	7000	1200
16	16.00"W-0150S-11.50"-M5	S	1.50	0.09	5	63	2100	42600	2700
237	16.00"W-0150L-17.00"-M5	L	3.00	0.36	10	82	1050	5325	1350
18	18.00"W-0150S-12.00"-M5	S	1.50	0.10	4	76	1960	58000	5400
299	18.00"W-0150L-18.00"-M5	L	3.00	0.40	8	96	880	6500	2700
20	20.00"W-0150S-12.00"-M5	S	1.50	0.09	5	94	2180	78000	7200
363	20.00"W-0150L-18.00"-M5	L	3.00	0.36	10	112	1090	9750	3600
24	24.00"W-0150S-12.00"-M5	S	1.50	0.08	5	120	2360	117000	10296
511	24.00"W-0150L-18.00"-M5	L	3.00	0.32	10	158	1180	14625	5148