

"BSH" - BRONZE - STANDARD PRESSURE BULK HOSE							
NOM. DIA. (IN.)	NBR. OF BRAIDS	NOM. O.D. (IN.)	STATIC	DYNAMIC		MIN. BURST PRESS. @ 70°F (PSIG.)	WEIGHT PER FOOT (LBS.)
			MIN. BEND RAD. (IN.)	MIN. BEND RAD. (IN.)	MAX. PRESS. (WP*) @ 70° F (PSIG.)		
1/4	0	0.49	1.00	5.50	100	4142	0.13
	1	0.57			1035		0.23
	2	0.65			1656		0.33
3/8	0	0.67	1.25	6.00	40	2738	0.25
	1	0.75			685		0.36
	2	0.83			1096		0.47
1/2	0	0.82	1.50	7.00	40	2825	0.38
	1	0.90			706		0.57
	2	0.98			1130		0.76
3/4	0	1.21	2.25	8.00	30	2307	0.50
	1	1.31			577		0.83
	2	1.41			923		1.16
1	0	1.51	3.00	10.00	20	1881	0.68
	1	1.61			470		1.12
	2	1.71			752		1.56
1-1/4	0	1.85	3.50	12.00	15	1443	0.80
	1	1.95			361		1.31
	2	2.05			577		1.82
1-1/2	0	2.18	4.00	13.50	10	1317	1.03
	1	2.31			329		1.73
	2	2.43			526		2.43
2	0	2.50	5.00	17.00	8	1267	1.81
	1	2.63			317		1.73
	2	2.75			507		2.43
2-1/2	0	3.18	8.00	22.00	8	1090	1.39
	1	3.31			272		2.56
	2	3.43			435		3.93
3	0	3.65	12.00	24.00	10	844	1.44
	1	3.78			211		2.84
	2	3.91			338		4.11
4	0	4.81	14.00	26.00	8	568	3.45
	1	4.94			142		5.03
	2	5.06			227		6.61

* WP: WORKING PRESSURE